Geoprobe 8150LS Rotary Sonic

VIDEOS AVAILABLE AT GEOPROBE.COM/8150LS WHEN YOU SEE THIS SYMBOL

Dual Winch System

Geoprobe[®] GV5 Sonic Head

• 50K Dyanamic Force

Head Centerline Side-Shift, Extend, Drill Mast Dump, Breakout Vertical Shift, Drill Mast Side-Shift, Head Tilt

10-ft. Tooling Compatible

Outriggers (Four Point Stabilization)

> 14-in. Double Wrench Breakout

Geoprobe[®] Designed Rod Handling System

geoprobe.com/8150ls

Full-Size Rotary Sonic Rig with 50K Dynamic Force

The Geoprobe[®] 8150LS is a full-size rotary sonic rig with high performance. It is capable of running 10-ft. tooling and the GV5 sonic head provides 50,000 lbs. of dynamic force.

Multi-Function Drill Mast

- High Speed Coring Head (Optional)
- Auto Drop Hammer Compatible (SPT)

Rock Coring Compatible

Engine Mounted Air Compressor

Water / Mud Pumps Multiple configurations available


Control Panel


Movable, Adjustable Swing-Arm
Remote Diagnostics

Videos, Photos, Specifications, and Resources geoprobe.com/8150ls

Weight & Dimensions

Base Unit Weight: 32,500 lb. (14,742 kg.) With Typical Options*: 33,500 lb. (15,195 kg.)





View full specifications online at geoprobe.com/8150ls

Tooling

Typical Geoprobe® Tooling for the 8150LS

- · Casing Sizes: 10 inch, 8 inch, 6 inch, 4.5 inch HD
- Weighted Wire Line Sampling (WWL60)
- Dual Tube Sonic Sampling (SDT60)
- 8x10, 6x8, 4x6 HD Sonic Sampling
- SP60 Groundwater Sampling

Rig shown with optional features. Weights & dimensions subject to change without notice. *Typical extras and options include hose pump, rod handler, second winch, and 48 in. toolbox. Standard features include triplex pump, breakout, air compressor, and head feed pressure control.

8150LS Options

High Speed Coring Head

226036 GV5 High Speed Coring Head Drive

Automatic Drop Hammer

226167Automatic Drop Hammer Only, 140 lb226289Drop Hammer Mounting Brackets216826Automatic Drop Hammer 340 lb. Expansion Kit217067Automatic Drop Hammer 300 lb. Expansion Kit21820Automatic Drop Hammer 170 lb. Expansion Kit210126Weight, 65 kg

Mast / Winch

220582 Wireline Winch Kit: 1,800 lbf with Quick Change Hook

Rotational Safety Cage

222917 Safety Cage

Rod Handler

225998 Rod Handler System (3" to 9", Double Jointed, Integral Safety Features)

Water / Mud Pumps

220581 SPX40 Hose Pump Kit 228405 Hose Reel Kit - Kerr Pump Mount

Air Compressor

400043 Air Line Oiler Kit

Toolboxes

220333 48 in. Toolbox

Additional Options

216816 Drill Mast Adjustable Brace Kit 218880 GV5 Spindle Adapter, 6.0 in., 4.5 in., 3.5 in. Assembly 222600 GV5 Spindle Assembly 220109 Back-up Alarm

Racks

226133 Inde: 226096 Inde: 226314 Inde:

Indexing Rack, 6.0 in. Casing Indexing Rack, 4.5 in. Casing Indexing Rack, 7.625 in. Casing





Wireline Winch Kit (220582)



Rod Handler System (225998)



SPX40 Hose Pump Kit (220581)



The 8150LS fits inside a 40 ft. shipping container for international transportation.